

XXPol 2300~2690MHz/3300~3800MHz 90°/65° 16.0/16.3dBi 2°~12°/2°~12° Integrated and replaceable RCU (Remote Control Unit) Antenna

Electrical Specifications-TDD					
General Parameters	Frequency range(MHz)		2300~2690	3300~3800	
	Polarization		±45°		
	Electrical downtilt(°)		2~12		
	Electrical downtilt tolerance(°)		±1		
Calibration and Electrical Parameters	Coupling factor between calibration port and each antenna port(dB)		-26±2		
	Max.amplitude tolerance from calibration port to input ports(dB)		≤0.9		
	Max.phase tolerance from calibration port to input ports(°)		≤8		
	Ports VSWR		≤1.5		
	Co-polarization isolation between ports(dB)		>20		
	Cross-polarization isolation between ports(dB)		>22		
	Inter array spacing(mm)		58(0.48λ@2495MHz,0.68λ@3550MHz)		
Radiation Parameters	Single Column Beam	Horizontal 3dB beam width(°)		95 ±15	70±15
		Gain(dBi)		14.3±0.9	14.8±1
		Vertical 3dB beam width(°)		7.6±0.6	5.8±0.5
		Cross polar ratio(0°)(dB)		>15	>15
		Cross polar ratio(±60°)(dB)		>6	>6
		Front to back ratio(dB)		>22	>25
		Vertical sidelobe suppression for first sidelobe above main beam(dB)		>14	>13
	Broadcast Beam	Gain(dBi)		16.0±0.9	16.3±1
		SPR(±60°)(%)		≥87	≥87
		Vertical 3dB beam width(°)		7.6±0.6	5.6±0.5
		Front to back ratio(dB)		>24	>26
		Vertical sidelobe suppression for first sidelobe above main beam(dB)		>14	>13
	Service Beam	0° direct beam gain(dBi)		19.8±0.9	20.1±0.9
		0° direct beam horizontal 3dB beam width(°)		27±4	22±4
		0° direct beam sidelobe suppression(dB)		>12	>12
		0° direct beam cross polar ratio(axial)(dB)		>18	>18
		0° direct beam front to back ratio(dB)		>27	>28
		±30° direct beam gain(dBi)		17±0.8	18.3±0.8


Mechanical Specifications

Connector	9×4.3-10-Female
Connector position	Bottom
Height × width × depth (mm)	998×270×140
Packing size (mm)	1340×365×220
Antenna weight (kg)	12.9
Installation kit weight (kg)	4.4
Packing weight (kg)	19
Wind load (N,at 150km/h) Frontal/Lateral/Maximum	294/91/349
Max. wind velocity (km/h)	216
Radome material	Fiberglass
Radome color	Gray
Mechanical tilt (°)	0~10
Operating temperature (°C)	-50~65
Mounting hardware (mm)	Φ50~Φ115


Integrated RET Properties

RET model	TRCU-TM10P1V01
RET type	Integrated (Replaceable)
RET protocol	AISG 2.0 / 3GPP
Power supply(V)	10-30 DC
Power consumption(W)	≤0.6 (Idle, 12V), ≤6 (in motion, 12V)
Adjustment time (Full Range)	<4Mins
Adjustment cycles	> 50,000
Temperature range (°C)	-40~65
Lightning protection	3KA(8/20μs) @ Pin5& Pin3; 5KA(8/20μs) @ Pin1/ Pin6& Pin7
Connectors	2×8 Pin circle connector according to IEC 60130-9 and AISG. Daisy chain in:Male,Daisy chain out:Female Pin1:12V;Pin3:RS485B;Pin5:RS485A;Pin6:10-30V;Pin7:GND; Pin2 &Pin4 & Pin8:N/C


Antenna Pattern Sample For Reference




Single column beam



0° Service beam



30° Service beam



BCH beam

